

670
Clear Water Repellent
Sprayer Directions

RECOMMENDED USES:

Siding, fences, garden furniture, specialty hardwoods, pressure treated lumber, and log/timber frame homes.

DO NOT APPLY OVER PREVIOUSLY PAINTED SURFACES.

WOOD Rx Clear Wood Protector will allow wood to gray naturally.

The best prescription, by far, for any wood surface, WOODRx Clear Wood Protector is a technologically advanced, water based sealer that effectively penetrates, seals and protects exterior wood surfaces from water damage. WOODRx Clear Wood Protector employs silicone technology which produces long lasting water repellency. WOODRx Clear Wood Protector also contains an effective fungicide which resists mildew growth in the harshest climates. Protects three to five times longer than competitive wood sealers.

SURFACE PREPARATION:

1. Apply a solution of 1 part household bleach or bleach alternative, 1 part dishwashing soap and 4 parts water.
2. Scrub and/or pressure wash as necessary to remove any surface contaminants.
3. Apply a test sample of WOOD Rx *ultra* to insure proper adhesion. If beading or crawling occurs, contact INSECO prior to applying.

PUMP SPRAY APPLICATION:

1. Shake container with WOOD Rx Clear Wood Protector thoroughly before use.
2. The tip of the pump sprayer is adjustable. Prior to starting, adjust the tip to the desired spray level. Turning the tip clockwise will reduce the flow of material while turning the tip counter clockwise will increase the flow of material. The tip should be adjusted to achieve an even, continuous fan spray.
3. Begin spraying and apply in an even, continuous manner. Saturate surface but avoid puddling. If puddling occurs, use a brush or a roller to distribute excess material immediately. Do not allow puddles to stand for an extended period of time.
4. Apply 1-2 coats as required to saturate surface and achieve a uniform appearance. Allow 1-2 hours between coats.
5. WOOD Rx Clear Wood Protector may be applied to damp or dry wood.

CLEAN UP:

Clean up drips and spills immediately using a damp cloth. Clean tools and equipment

with soap and fresh water.

DRY TIME:

Allow 12 hours before subjecting to light foot traffic.

COVERAGE:

WOODRx Clear Wood Protector covers approximately 400 square feet per gallon. Coverage will vary depending on texture and porosity of the substrate.

CAUTION:

Do not apply if the threat of rain exists. Keep from freezing. Keep out of reach of children. Do not use if temperature is below 40 degrees F.

INSECO, Inc.
5601 Banner Drive
Ft. Myers, FL 33912
800-883-5150