

625
WOOD Rx ultra
Directions For Use

RECOMMENDED USES:

Decks, docks, siding, fences, garden furniture, specialty hardwoods, pressure treated lumber and log/timber frame homes.

DO NOT APPLY OVER PREVIOUSLY PAINTED SURFACES.

The best prescription, by far, for any wood surface, WOODRx is a technologically advanced, water based finish that effectively penetrates, seals and protects exterior wood surfaces. WOODRx resists moisture penetration and retards the aging (silvering) process of wood. WOODRx contains an effective fungicide which resists mildew growth on the film and a powerful UV screener that filters out the sun's harmful rays. WOODRx protects and beautifies three to five times longer than conventional wood sealers.

WOOD Rx *ultra* combines the superior durability characteristics of our original WOOD Rx formulation with new and improved application and wear properties. **WOOD Rx *ultra*** spreads effortlessly and evenly and its unique formulation resists the lapping characteristics inherent in most transparent wood sealers. The ***ultra*** formulation also exhibits uniform wear characteristics which makes maintaining wood quick and easy.

SURFACE PREPARATION:

1. Apply a solution of 1 part household bleach or bleach alternative, 1 part dishwashing soap and 4 parts water.
2. Scrub and/or pressure wash as necessary to remove any surface contaminants.
3. appealing appearance. If beading or crawling occurs, contact INSECO prior to applying. Apply a test sample of WOOD Rx *ultra* to insure proper adhesion and an

PUMP SPRAY APPLICATION:

1. **Shake container with WOOD Rx *ultra* thoroughly before use.**
2. Apply a test sample of WOOD Rx *ultra* to insure proper adhesion and appealing appearance. If beading or crawling occurs, contact INSECO prior to applying.
3. **The tip of the pump sprayer is adjustable. Prior to starting, adjust the tip to the desired spray level. Turning the tip clockwise will reduce the flow of material while turning the tip counter clockwise will increase the flow of material. The tip should be adjusted to achieve an even, continuous fan spray.**
4. **Begin spraying and apply in an even, continuous manner. Saturate surface but avoid puddling. If puddling occurs, use a brush or a roller to distribute excess material immediately. Do not allow puddles to stand for an extended period of time.**
5. **Apply 1-2 coats as required to saturate surface and achieve a uniform**

appearance. Allow 1-2 hours between coats.
6. WOOD Rx ultra may be applied to damp or dry wood.

CLEAN UP:

Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

DRY TIME:

Allow 12 hours before subjecting to light foot traffic.

COVERAGE:

WOODRx ultra covers approximately 400 square feet per gallon. Coverage will vary depending on texture and porosity of the substrate.

CAUTION:

Do not apply if the threat of rain exists. Keep from freezing. Keep out of reach of children. Do not use if temperature is below 40 degrees F.

CAUTION: KEEP OUT OF REACH OF CHILDREN!

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Technical data contained herein is true and accurate at the date of issue, but is subject to change without notice. An INSECO representative should be contacted with any questions concerning product information or application procedures. Our products conform to INSECO quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.

INSECO, Inc.
5601 Banner Drive
Ft. Myers, FL 33912
800-883-5150